



MOTORTRONICS™

Solid State AC Motor Controls

Soft Starters for Pump Jack Applications



**VMX Soft Starter available
from 18 to 1250A
(up to 1200HP)**



Standalone Soft Starters or Packaged to customer specification

Packaged Solutions & Standalone Soft-Starters

Dead Front Door Option Available



VMX-H



VMX

Rugged Power Components

Inverse parallel paired SCRs
Auto-synchronizing Gate Firing method
500% 60sec Overload Capacity
1600V PIV rating

Line Voltage

200-600VAC 3 phase 50/60HZ

Current Rating

18-1250A (5HP to 1200HP)

AC Supply Voltage

120V Control Voltage (CPT included)

Ramp Control

Closed Loop Torque/Current Ramping
Voltage Ramp with Current Limit

Across the Line Start Capability

Fully Rated Bypass/Emergency Start Contactor
Full voltage/Softstart Selector Switch
Independent Overload Relay

Advanced Motor Protection


Retentive Thermal Memory
Dynamic Reset Capacity

Built-in Functions

Operator Interface
Ramp Control Choices (4 built-in), Dual Ramps, Jog Function
Kick Start Function, Pump-Flex™ Deceleration Ramp, Restart Delay Timer
Time Clock Controller, RS-485 Serial Communications

Closed Loop Torque /Current (CLT™)

This function provides a linear increase in output torque during acceleration. It maximizes the available torque using an internal PID feedback loop, insuring a smooth, linear ramp up to full speed.



CORPORATE HEADQUARTERS

Motortronics / Phasetronics

1600 Sunshine Drive
Clearwater, Florida 33765
Tel: 727.573.1819 or 888.767.7792
Fax: 727.573.1803 or 800.548.4104
E-mail: sales@motortronics.com
www.motortronics.com

INTERNATIONAL LOCATIONS

Motortronics Int'l Korea Co Ltd

601, Daeryung Techno Tower 5-cha
Gasan-dong, Geumcheon-gu
Seoul, Korea 9153-774
Tel: 82-2-867-5808 / Fax: 82-2-867-6004
www.motortronics-korea.com



MOTORTRONICS™

Solid State AC Motor Control

M & P Machinery & Electronics Control

113 Zaoshan Road
Qingdao, China 266100
Tel: 86-532-87660633
Fax: 86-532-87660733
www.mp-cn.com

PN: MT-PJ-052313