

Enclosed
Soft Starters in
Standard Duty
& Heavy Duty
Ratings



The VMX Series Specifications

The "Configured" soft starter that is designed for any application

by  **MOTORTRONICS**

"Heavy Duty" Configured VMX Series Soft Starters

- Standard VMX Series features
- 500% rated for 30 seconds
- Prepackaged combination or non-combo starters
- Built-in circuit breaker or fusible disconnect option with door-mounted lockable operator handle
- NEMA 4/12 enclosure
- Integral line-start (ATL) rated bypass contactor
- Advanced motor protection
- Control power transformer
- Interface board for easy control connections
- Door mounted keypad & pilot devices



- Digital Keypad
- Start / Stop pushbutton
 - Local / Off / Remote Switch
 - Motor Run Pilot Light
 - Power On Pilot Light
 - Start Fault Pilot Light
 - E-Stop Fault Pilot Light
 - External Interlock Pilot Light

"Standard Duty" Configured VMX Series Soft Starters

Designed for lighter duty loads (like many pumps, fans and blowers) where a soft starter rated at 350% for 30 seconds is more than adequate. Same great performance features and accessories you would find in the "Heavy Duty" offering, only supplied with a shunt duty rated integral bypass contactor instead of a line rated contactor. A cost-effective and reliable motor starting solution for standard duty applications.