



# Current Transformer

## Model 10

### CERTIFICATIONS:



**APPLICATION:**

Metering

**FREQUENCY:**

50-400 Hz.

**INSULATION LEVEL:**

600 Volts. 10 kV BIL. full wave

**WINDOW DIAMETER:**

1.56"

**APPROXIMATE WEIGHT:**

2.5 lbs.


**CONNECTIONS:**

-Terminals are brass studs No. 8-32 UNC with one flat washer, lockwasher, and regular nut

Model	10SFT
Window Size	1.56
Width	4.08
Height	4.59
Depth	2.10


**MODEL 10**  
**Window Diameter 1.56"**  
**Approximate weight: 2.5 lbs.**

CATALOG NUMBER	CURRENT RATIO	V.A. FOR $\pm 1\%$ CLASS	ANSI METERING CLASS AT 60 HZ					SECONDARY WINDING RESISTANCE (OHMS @ 75° C)	CONTINUOUS THERMAL RATING FACTOR	
			BO.1	BO.2	BO.5	BO.9	B1.8		@30°C	@55°C
10SFT-500	50:5	2.0 $\pm$ 2%	4.8	-	-	-	-	0.007	2	2
10SFT-750	75:5	2.5	1.2	4.8	-	-	-	0.01	2	2
10SFT-101	100:5	3	1.2	2.4	4.8	-	-	0.018	2	2
10SFT-151	150:5	5	0.6	0.6	2.4	4.8	-	0.031	2	2
10SFT-201	200:5	7.5	0.3	0.6	1.2	2.4	4.8	0.043	2	1.5
10SFT-251	250:5	10	0.3	0.3	1.2	1.2	2.4	0.053	2	1.5
10SFT-301	300:5	15	0.3	0.3	0.6	1.2	2.4	0.07	2	1.5
10SFT-401	400:5	20	0.3	0.3	0.3	0.6	1.2	0.114	1.5	1
10SFT-501	500:5	30	0.3	0.3	0.3	0.6	1.2	0.128	1.33	1
10SFT-601	600:5	40	0.3	0.3	0.3	0.6	0.6	0.192	1.33	0.8




Products are manufactured in a plant whose quality management system has been certified to be in compliance with ISO 9001:2015 by NQA

**Model 10**



**EXCITATION CURVE**



Model 10